



Rectilinear, forward throw luminaire for parking areas, fast food lots and other perimeter applications requiring sharp cutoff behind the pole.

Features

- Shallow, formed and welded aluminum housing with optional embossed decorative band. Optional color vinyl trim stripe available.
- Formed aluminum door with clear, flat tempered glass lens, fully gasketed to housing. Hinged door secured with captive screws.
- Specular, anodized aluminum reflector for horizontal lamp, provides Type IV light pattern with **sharp rear cutoff**.
- Extruded aluminum arm provided for pole mount. Cast aluminum wall bracket.
- Mogul porcelain socket, pulse rated with spring-loaded, nickel-plated center contact and reinforced lamp grip screw shell.
- CWA type ballast, HPF, starting rated at -20°F (-40°F for HPS).
- TGIC thermoset polyester powder paint finish with choice of five standard and two premium standard colors.
- UL and CSA listed for wet locations.

Ordering Information

Example: **1** LN1 - **2** A - **3** H40 - **4** H4 - **5** F - **6** Q - **7** DB - **8** P1 - L

Series Mounting Lamp/Watt. LampOrient./Dist. Lens Voltage Color Options

- 1 Series**
LN1 = Lincoln 1
LN2 = Lincoln 2
- 2 Mounting**
A = Arm Mount
- 3 Lamp Type/Wattage**
LN1
Metal Halide
H17
H25
H40
Super Metal Halide
MS17
MS25
MS40
Pulse Start
P20
P25
P32
P35
P40
High Pressure Sodium
S15
S25
S40
LN2
Metal Halide
H1K
Super Metal Halide
MS1K
High Pressure Sodium
S1K

- 4 Lamp Orient./Distribution**
H4 = Horizontal Lamp Type 4

- 5 Lens**
F = Flat

- 6 Voltage**
Q = Quad-Tap
5 = 480V
T = Tri-Tap

- 7 Color**
Standard:
WH = White
DB = Dark Bronze
PS = Platinum Silver
GR = Gray
BL = Black
Premium
FG = Forest Green
RD = Red
Custom Color:
Consult Factory

- 8 Options**
L = Lamp (included)
QZ = Quartz
Button Cell
P1 = 120V
P2 = 208V
P3 = 240V
P4 = 277V
P6 = 347V

- Fuse**
F1 = 120V
F2 = 208V
F3 = 240V
F4 = 277V
F5 = 480V
F6 = 347V
- Photo Receptacle**
PR1 = 120V
PR2 = 208V
PR3 = 240V
PR4 = 277V
PR5 = 480V
PR6 = 347V
- Reveal Color**
RDB = Dark Bronze
RWH = White
RPS = Platinum Silver
RGR = Gray
RBL = Black
RFG = Forest Green
RRD = Red
RVB = Vivid Blue
EB = Embossed Band

- PTL-X = Twist-Lock Cell (order separately)
PTL-8PC = Quad-Tap
PTL-5 = 480V
PTL-6 = 347V
PSC = Twist-Lock Shorting Cap

Mounting Arms - ordered separately
Model = ARM-L-6-X-XX

Wall Bracket - ordered separately
(arm included)
Model = WB-S-XX

Dimensions

	A	B	C	EPA	Wt./Lbs.
LN1	14.5"	23.25"	8.75"	1.7	39
LN2	18.84"	28.43"	10.75"	2.6	82

