

MEDALLION

Features

- Architectural, one-piece die-cast aluminum housing with nominal .125" wall thickness. Contour lines and radius corners complete unique design.
- Die-cast aluminum door hinges to housing and secures with two, captive screws. Clear, flat or convex, tempered glass lens seals to door and housing with one-piece silicone gasketing.
- Specular, anodized aluminum reflectors for horizontal lamp, provide Type II, III, IV or V square light patterns and for vertical lamp provide Type IV or V square light patterns. **Horizontal Type II, Type III and vertical Type VS reflectors feature unique, multifaceted patented designs.** IESNA Full Cutoff lighting classification achieved with vertical lamp and flat lens.
- Die-cast aluminum arm for pole mount features access door to facilitate installation. Wall mount with cast aluminum bracket and arm. Mast arm mount with cast aluminum slipfitter.
- Mogul porcelain socket, pulse rated with spring-loaded, nickel-plated center contact and reinforced lamp grip screw shell. Medium base for ED-17 lamp.
- CWA type, HPF ballast, starting rated at -20°F (-40°F for HPS).
- TGIC thermoset polyester powder paint finish with choice of five standard and two premium standard colors.
- UL and CUL listed for wet locations.
- Patent pending on multifaceted reflector designs.



Specification luminaire provides outstanding uniformity for parking areas and entrance drives.



Ordering Information

Example: ① **CM** - ② **A** - ③ **P17** - ④ **V5** - ⑤ **C** - ⑥ **Q** - ⑦ **WH** - ⑧ **P1** - **L**
 Series - Mounting - Lamp/Watt. - LampOrient./Dist. - Lens - Voltage - Color - Options

① **Series**
 CM = Medallion

② **Mounting**
 A = Arm Mount

③ **Lamp Type/Wattage**
Metal Halide
 H17 H25 H40
Super Metal Halide
 MS17 MS25 MS40
Pulse Start
 P10 P12 P15
 P17 (VL only)
 P20 P25 P32
 P35 P40
High Pressure Sodium
 S10 S15
 S25 S40

④ **Lamp Orient./Distribution**
 H2 = Horizontal Lamp Type 2
 H3 = Horizontal Lamp Type 3
 H4 = Horizontal Lamp Type 4
 H5 = Horizontal Lamp Type 5
 V4 = Vertical Lamp Type 4
 V5 = Vertical Lamp Type 5

⑤ **Lens**
 F = Flat
 C = Convex

⑥ **Voltage**
 Q = Quad-Tap
 5 = 480V
 T = Tri-Tap

⑦ **Color**
Standard:
 WH = White
 DB = Dark Bronze
 PS = Platinum Silver
 GR = Gray
 BL = Black
Premium
 FG = Forest Green
 RD = Red
Custom Color:
 Consult Factory

⑧ **Options**
 L = Lamp (included)
 QZ = Quartz
 RP = Removable Ballast Panel
 TL = Tool-Less Door/Reflector Panel
 QR = Quick Release Latch (V4 only)
 VG = Vandal Guard (flat lens only)
 HS = Internal House-Side Shield (flat lens only)

Fuse
 F1 = 120V
 F2 = 208V
 F3 = 240V
 F4 = 277V
 F5 = 480V
 F6 = 347V
Photo Receptacle
 PR1 = 120V
 PR2 = 208V
 PR3 = 240V
 PR4 = 277V
 PR5 = 480V
 PR6 = 347V





PTL-X = Twist-Lock Cell (order separately)
PTL-8PC = Quad-Tap
PTL-5 = 480V
PTL-6 = 347V
PSC = Twist-Lock Shorting Cap

Mounting Arms - order separately
Model = ARM-C-5-X-XX
NOTE: 90° mounting configuration requires 10" arm.

Wall Bracket - order separately
 (arm included)
Model = WB-C-XX

Dimensions

	A	B	C	EPA	Wt./Lbs.
CM	16"	21.75"	10"	1.9	39
CM-VLC	16"	21.75"	13.25"	2.0	41
CM-VLF	16"	21.75"	10"	1.9	39



CM-VLF

CM-VLC

CM