

WASHINGTON

Features

- Spun aluminum, round dome-top housing, with narrow decorative reveal. Optional color vinyl trim stripe available.
- Formed aluminum door with clear, flat tempered glass lens, fully gasketed to housing. Hinged door secured with captive screws.
- Specular, anodized aluminum reflectors for horizontal lamp, provide Type II, III, IV or V square light patterns and for vertical lamp provide Type IV or V square light patterns.
- **Horizontal Type II and Type III reflectors with WN1 and WN2 and vertical Type VS reflector with WN2-VL feature unique, multifaceted patented designs.** Segmented horizontal Type III, vertical Type III and vertical Type VS reflectors with WN3.
- IESNA Full Cutoff lighting classification achieved with vertical lamp.
- Extruded aluminum arm for pole mount. Cast aluminum wall bracket.
- Pole top luminaire has four aluminum tube arms and cast slipfitter for 2-3/8" OD tenon.
- Mogul porcelain socket, pulse rated with spring-loaded, nickel-plated center contact and reinforced lamp grip screw shell. Medium base for ED-17 lamp.
- CWA type ballast, HPF, starting rated at -20°F (-40°F for HPS).
- TGIC thermoset polyester powder paint finish with choice of five standard and two premium standard colors.
- UL and CSA listed for wet locations.



Specification, round dome-top luminaire for visual enhancement of parking areas and entrance drives.



AREA

Ordering Information

Example: **WN2** - **ST** - **MS40** - **H3** - **F** - **Q** - **FG** - **RBL** - **L**

Series Mounting Lamp/Watt. LampOrient.Dist. Lens Voltage Color Options

1 Series

WN1 = Washington 1
WN2 = Washington 2
WN3 = Washington 3

2 Mounting

A = Arm Mount
ST = Spider Tenon Mount 2-3/8"

3 Lamp Type/Wattage

WN1
Metal Halide
H17
Super Metal Halide
MS17
Pulse Start
P10
P12
P15
P17 (VL only)
High Pressure Sodium
S10
S15
WN2
Metal Halide
H25
H40
Super Metal Halide
MS25
MS40

Pulse Start

P17 (VL only)
P20
P25
P32
P35
P40
High Pressure Sodium
S15
S25
S40
WN3
Metal Halide
H1K (HL only)
Super Metal Halide
MS1K (HL only)
Pulse Start*
P20
P25
P32
P35
P40
High Pressure Sodium
S1K (HL only)
* for VL only.

4 Lamp Orient./Distribution

H2 = Horizontal Lamp Type 2
H3 = Horizontal Lamp Type 3
H4 = Horizontal Lamp Type 4
H5 = Horizontal Lamp Type 5

5 Lens

F = Flat

6 Voltage

Q = Quad-Tap
5 = 480V
T = Tri-Tap

7 Color

Standard:
WH = White
DB = Dark Bronze
PS = Platinum Silver
GR = Gray
BL = Black
Premium
FG = Forest Green
RD = Red
Custom Color:
Consult Factory

8 Options

L = Lamp (included)
QZ = Quartz
VG = Vandal Guard
HS = House-Side Shield

Button Cell

P1 = 120V
P2 = 208V
P3 = 240V
P4 = 277V
P6 = 347V
Fuse
F1 = 120V
F2 = 208V
F3 = 240V
F4 = 277V
F5 = 480V
F6 = 347V

Reveal Color

RDB = Dark Bronze
RWH = White
RPS = Platinum Silver
RGR = Gray
RBL = Black
RFG = Forest Green
RRD = Red
RVB = Vivid Blue

PTL-X Twist-Lock Cell (order separately)

PTL-8PC = Quad-Tap
PTL-5 = 480V
PTL-6 = 347V
PSC = Twist-Lock Shorting Cap

Mounting Arms - ordered separately


Model = ARM-W-6-X-XX

Wall Bracket - ordered separately (arm included)


Model = WB-R-XX

Dimensions


	A	B	C	EPA	Wt./Lbs.
WN1	18"	11.5"	23.5"	1.0	40
WN2	22.5"	14"	27.25"	1.3	60
WN3	26"	17.5"	29.75"	1.8	80



Arm Mount (PM)



Arm Mount (PM)



Spider Mount (SM-MF)