

# SOFFITIER

CANOPY



Square recessed luminaire for canopies, soffits, parking garages and facades.

## Features

- Square, formed aluminum housing with integral trim flange.
- Aluminum lens frame with prismatic, flat glass lens, fully gasketed to housing. Hinged frame secured with captive screw. Optional drop prismatic acrylic or drop prismatic polycarbonate lenses.
- Diffused, anodized aluminum reflectors for horizontal or vertical lamp provide asymmetric or symmetric light pattern, respectively.
- Recessed mount provided with adjustable aluminum brackets. Designed for 1/4" to 3/4" thick ceiling with 14-1/4" square, rough opening.
- Thermal protector included.
- Medium porcelain socket, pulse rated with spring-loaded, nickel-plated center contact and reinforced lamp grip screw shell.
- CWA type ballast, HPF, starting rated at -20°F (-40°F for HPS).
- TGIC thermoset white polyester powder paint finish.
- UL and CUL listed for damp locations.

## Ordering Information

Example: **1** ST - **2** CM - **3** P17 - **4** VL - **5** FGP - **6** Q - **7** WH - **8** F1 - L

Series      Mounting      Lamp/Watt.      Lamp Orient./Dist.      Lens      Voltage      Color      Options

### 1 Series

ST = Soffitier

### 2 Mounting

CM = Ceiling Mount

### 3 Lamp Type/Wattage

Metal Halide  
H17  
Pulse Start  
P70  
P10  
P12  
P15  
P17 (VL only)  
High Pressure Sodium  
S70  
S10  
S15

### 4 Lamp Orient./Distribution

HL/AS = Horizontal Lamp - Asymmetric  
VL/SY = Vertical Lamp - Symmetric

### 5 Lens

DA = Drop Acrylic  
FGP = Flat Glass Prismatic  
DP = Drop Polycarbonate

### 6 Voltage

Q = Quad-Tap  
T = Tri-Tap

### 7 Color

WH = White

### 8 Options

L = Lamp (included)  
QZ = Quartz  
Fuse  
F1 = 120V  
F2 = 208V  
F3 = 240V  
F4 = 277V  
F5 = 480V  
F6 = 347V

## Dimensions

	A	B	C	Wt./Lbs.
ST	13.8"	8"	16.6"	34

