

Features

- Square Straight Steel Shaft
- One-piece construction
- Side, Tenon, or Pad mounting available
- Ground lug standard
- Galvanized anchor bolts and template included (4-bolt design)

- Base cover standard (Square)
- Gasketed hand hole cover standard (3"x5")
- Lektrocote finish standard
- CSA certification available



Catalog Number	Pole Ht.		Nominal Shaft Dim.	Wind Load Rating ¹					Wall Thick.	Bolt			Base Plate (sq.)	Anchor Bolt Size	Bolt Proj.	Pole Wt (lbs)
	ft	m		70 MPH	80 MPH	90 MPH	100 MPH	120 MPH		Circle (Sug.)	Bolt Circle	Bolt Sq.				
SSS-10-40-1-XX-XX	10	3.0	4	38	28.5	22	17	11	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	91
SSS-10-50-1-XX-XX	10	3.0	5	60	46	36	28	19	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	106
SSS-12-40-1-XX-XX	12	3.7	4	28	21	15	12	7.5	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	104
SSS-12-50-1-XX-XX	12	3.7	5	45	33	25	20	13	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	122
SSS-14-40-1-XX-XX	14	4.3	4	23	17	12.5	9.5	6	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	116
SSS-14-40-7-XX-XX	14	4.3	4	34.5	25.5	20	15	9.5	.179	11"	8 1/2 - 12"	6 - 8.4"	11 x 1"	3/4 x 30 x 3"	4"	158
SSS-14-50-1-XX-XX	14	4.3	5	38	28.5	21.5	16.5	10.5	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	138
SSS-16-40-1-XX-XX	16	4.9	4	19.5	14	10.5	7.5	4	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	128
SSS-16-40-7-XX-XX	16	4.9	4	29.5	21.5	16	12	8	.179	11"	8 1/2 - 12"	6 - 8.4"	11 x 1"	3/4 x 30 x 3"	4"	176
SSS-16-50-1-XX-XX	16	4.9	5	32	23.5	17.5	13.5	8	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	153
SSS-16-50-7-XX-XX	16	4.9	5	47.5	35.5	27	21.5	13.5	.179	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	214
SSS-18-40-1-XX-XX	18	5.5	4	16.5	11.5	8.5	6	3	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	147
SSS-18-40-7-XX-XX	18	5.5	4	25.5	18	13.5	10.5	6	.179	11"	8 1/2 - 12"	6 - 8.4"	11 x 1"	3/4 x 30 x 3"	4"	201
SSS-18-50-1-XX-XX	18	5.5	5	27.5	20	14	11	6	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	175
SSS-18-50-7-XX-XX	18	5.5	5	42	31	23.5	18	11	.179	11"	8 1/2 - 12"	6 - 8.4"	12 x 1"	3/4 x 30 x 3"	4"	243
SSS-20-40-1-XX-XX	20	6.1	4	13.5	9.5	6.5	4.5	1.8	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	160
SSS-20-40-7-XX-XX	20	6.1	4	22	16	11.5	8.5	4.5	.179	11"	8 1/2 - 12"	6 - 8.4"	11 x 1"	3/4 x 30 x 3"	4"	173
SSS-20-50-1-XX-XX	20	6.1	5	23.5	17	12	9	4.5	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	191
SSS-20-50-7-XX-XX	20	6.1	5	36.5	27	20	15.5	9	.179	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	3/4 x 30 x 3"	4"	266
SSS-20-60-7-XX-XX	20	6.1	6	51	38	28.5	22	14.5	.179	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1 x 36 x 4"	4"	312
SSS-25-40-1-XX-XX	25	7.6	4	8.5	5	3	1.5	NR	.119	11"	8 - 11"	5.6 - 7.8"	10.25 x 0.75"	3/4 x 30 x 3"	4"	238
SSS-25-40-7-XX-XX	25	7.6	4	14.5	10	6.5	4.5	1.4	.179	11"	8.5 - 12"	6 - 8.4"	11 x 1"	3/4 x 30 x 3"	4"	266
SSS-25-50-1-XX-XX	25	7.6	5	15	10.5	6.5	4	NR	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	231
SSS-25-50-7-XX-XX	25	7.6	5	25	18	12.5	8.5	4	.179	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	324
SSS-25-50-3-XX-XX	25	7.6	5	36.5	26	19	14	8	.250	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	437
SSS-25-60-7-XX-XX	25	7.6	6	38.5	28	20.5	15	8	.179	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1 x 36 x 4"	4"	404
SSS-27-40-7-XX-XX	27	8.2	4	-	9.4	-	4.2	1.2	.179	11"	8.5 x 12"	6 - 8.4"	11 x 1"	1 x 36 x 4"	4"	290
SSS-30-40-7-XX-XX	30	9.1	4	6.5	4.5	2.5	1.5	NR	.179	11"	8.5 x 12"	6 - 8.4"	11 x 1"	1 x 36 x 4"	4"	313
SSS-30-50-1-XX-XX	30	9.1	5	7.5	5.5	2.5	NR	NR	.119	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	274
SSS-30-50-7-XX-XX	30	9.1	5	18	12	8	4.5	NR	.179	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	398
SSS-30-50-3-XX-XX	30	9.1	5	22	16	13	8	3.8	.250	11"	10 - 13.5"	7.1 - 9.5"	12 x 1"	1 x 36 x 4"	4"	537
SSS-30-60-7-XX-XX	30	9.1	6	30	20	14	9	3.4	.179	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1 x 36 x 4"	4"	467
SSS-30-60-3-XX-XX	30	9.1	6	42	30	22	16	8	.250	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1.25 x 42 x 6"	4"	630
SSS-35-60-7-XX-XX	35	10.7	6	20.5	13	8	4.5	NR	.179	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1 x 36 x 4"	4"	538
SSS-35-60-3-XX-XX	35	10.7	6	26	18	12	7.5	3.4	.250	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1.25 x 42 x 6"	4"	726
SSS-40-60-7-XX-XX	40	12.2	6	11	8	3.5	NR	NR	.179	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1 x 36 x 4"	4"	614
SSS-40-60-3-XX-XX	40	12.2	6	14	10.5	5.5	2.5	NR	.250	12"	11 - 13.5"	7.8 - 9.5"	12 x 1"	1.25 x 42 x 6"	4"	802

1 Allowable EPA with 1.3 gust factor. To determine max. pole loading weight, multiply allowable EPA by 30 lbs.

Note Factory supplied template must be used when setting anchor bolts. Hubbell Lighting will deny any claim for incorrect anchorage placement resulting from failure to use factory supplied template and anchor bolts.

Ordering Information

Example: S - S - S - 25 - 40 - 1 - A1 - DB

Complete part number requires shaft above plus mounting type, finish, and appropriate options below.

	Cross Sect.	Style	Material	Nom. Length	Nom. Shaft	Shaft Thick.	Mount Type	Finish
Luminaire Mounting Type								
AX	Side - Single ¹							
BX	Side - Double at 90° ¹							
CX	Side - Double at 180° ¹							
DX	Side - Triple at 90° ¹							
FX	Side - Quad at 90° ¹							
P1	Pad Mount - Spider Type							
P2	Pad Mount - Yoke Type							
P3	Pad Mount - Yoke Type (Former XL only)							
TA	Tenon (2 3/8" OD)							
TB	Tenon (2 7/8" OD)							
TR	Removable Tenon (2 3/8 x 4 1/4) ²							
CD	Concord Luminaire							
OT	No drilling (includes pole cap)							
Finish								
DB	Dark Bronze							
BL	Black							
WH	White							
GR	Gray							
PS	Platinum Silver							
RD	Red (Premium Color)							
FG	Forest Green (Premium Color)							
CC	Custom Color (Consult Factory)							
PR	Primer Only							
Options								
Q55	Internal Coating (Hubbell Seal)							
Q18	15 Amp GFCI Receptacle and Cover ³							
Q22	Extra Handhole ³							
Q26	1/2" Coupling ³							
Q27	3/4" Coupling ³							
Q30	2" Coupling ³							
Q32	Mid-pole Luminaire Bracket ³							
Q40	Vibration Damper							
LAB	Less Anchor Bolts							
CSA	CSA Certified (consult factory)							

1 DRILL PATTERNS: Replace X with 1 = Luminaires with a straight pole (4-bolt), 2 = Cimarron CR1 and Raven Series luminaires, 4 = MSS & DS luminaires, 5 = Detroit III luminaires, 6 = MSV, RCS, RCL & DM luminaires

2 Removable tenon used in conjunction with side arm mounting. First specify desired arm configuration followed by the "TR" notation. Example: SSS-25-40-7-C6-TR-DB

3 Specify option location using logic found in pole introduction pages.