

MINI-ROCKFORD

Features



Square luminaire for walls, fast food lots, parking garages, entrances and loading docks.

- Cast aluminum housing. Surface wall mount with outlet box cover plate. Side entry for 1/2" NPT surface conduit.
- Frameless, injection-molded polycarbonate lens. Gasketed and secured with four captive screws.
- Formed, anodized aluminum reflector for horizontal lamp, provides forward throw light pattern with minimal light above horizontal plane.
- Medium porcelain socket, pulse rated with spring-loaded, nickel-plated center contact and reinforced lamp grip screw shell.
- NPF, HR or Reactor type ballast, starting rated at -20°F (-40°F for HPS).
- TGIC thermoset dark bronze polyester powder paint finish.
- UL and CSA listed for wet locations.

WALL MOUNT

Ordering Information

Example: **MRK** - **WM** - **P10** - **HL** - **P** - **Q** - **DB** - **F1** - **L**
Series Mounting Lamp/Watt. Lamp Orient. Lens Voltage Color Options

- 1 Series**
MRK = Mini-Rockford
- 2 Mounting**
WM = Wall Mount
- 3 Lamp Source/Wattage**
Pulse Start
P50
P70
P10
High Pressure Sodium
S50
S70
S10
S15
- 4 Lamp Orientation/Distribution**
HL = Horizontal Lamp
- 5 Lens**
P = Injection-Molded Polycarbonate (frameless)
- 6 Voltage**
Q = Quad-Tap
T = Tri-Tap*
* P50 and S50 not available in tri-tap.
- 7 Color**
DB = Dark Bronze
- 8 Options**
L = Lamp (included)
QZ = Quartz
Fuse
F1 = fuse 120V
F2 = fuse 208V
F3 = fuse 240V
F4 = fuse 277V
F6 = fuse 347V
Button Cell
P1 = button cell 120V
P2 = button cell 208V
P3 = button cell 240V
P4 = button cell 277V
P6 = button cell 347V

Dimensions

	A	B*	Wt./Lbs.
MRK	10"	6.12"	12
*7.6" for 150w			

