

# PERIMASHIELD POLYCARBONATE

## Features

- One-piece, die-cast aluminum housing. Surface wall mount over recessed outlet box. Side entries for 1/2" NPT surface conduit and 90°C rating for through wiring. Side entry hub for field-installed photoelectric button cell. Housing gasket meets IP-55 Code protection.
- One-piece, injection-molded, UV stabilized polycarbonate door and clear lens hinges to housing and secures with two captive screws. Interior door surface finished in standard bronze color.
- Formed, hammer-tone aluminum reflector for horizontal lamp. Field-adjustable socket position provides variable cutoff angles.
- Typical spacing-to-mounting height ratio of four-to-one.
- Lamp included.
- Medium porcelain socket, pulse rated with spring-loaded, nickel-plated lamp grip screw shell.
- NPF or HPF Class H ballast, starting rated at -20°F (-40°F for HPS). Aluminum cover isolates ballast components during relamping.
- TGIC thermoset dark bronze polyester powder paint finish.
- UL and CSA listed for wet locations.



Wall luminaire designed for sharp cutoff lighting around apartments, shopping centers and parking garages.



WALL MOUNT

## Ordering Information

**Example:** ① PRS - ② P100 - ③ 1 - ④ 2 - ⑤ 6 - ⑥ DB - ⑦ RS - L

Series    Lamp/Watt.    Ballast Type    Socket    Voltage    Color    Options

① **Series**  
PRS = Perimashield Polycarbonate

② **Lamp Source/Wattage**  
Metal Halide  
H175  
Pulse Start  
P100  
High Pressure Sodium  
S100  
S150

③ **Ballast Type**  
1 = High Power Factor  
5 = Normal Power Factor (120V HPS only)

④ **Socket**  
2 = Porcelain

⑤ **Voltage**  
1 = 120V (NPF only)  
6 = 120/277/347V  
8 = Quad-Tap

⑥ **Color**  
DB = Dark Bronze

⑦ **Options**  
L = Lamp (included)  
PBT1 = Photoelectric Button Cell 120V  
PBT2/3/4 = Photoelectric Button Cell 208/240/277V  
QSS = Quartz Standby Time Delay (less lamp)  
PVLV = Lens Visor Provides IESNA Cutoff Lighting Classification  
RS = Hot Restrike System Quickly Restores Lumen Output After Power Outage

## Dimensions

	A	B	C	Wt./Lbs.
PRS	14.87"	15.62"	7.18"	18

