

PERIMALUX

Features

- Rugged, injection molded texture and color polycarbonate housing.
- UV stabilized prismatic polycarbonate refractor for strength and long life.
- White Lektrocote finished reflector for excellent reflectivity and uniformity.
- Vandal-resistant refractor screw restricts un-authorized access to the lamp.
- Easy installation over standard 4" rough-in junction box.
- UL and CSA listed wet locations; indoor/outdoor; 25° C ambient.



The Perimalux is a compact, bronze polycarbonate wall pack that is ideal for mounting heights of 8 to 12 feet. This versatile unit comes complete with lamp and makes it a natural choice for exterior doorways and interior lighting jobs.

WALL MOUNT

Ordering Information

Example: **1** NRG - **2** 304 - **3** 120V - **4** DB - L

Series Lamp/Watt. Voltage Color

1 Series
NRG = Perimalux

2 Model **Lamp Source/Wattage** **Ballast**

| | | |
|-----|----------------------------|------------|
| 304 | Compact Fluorescent (CF42) | Electronic |
| 350 | Metal Halide (H50) | Reactor |

3 Voltage
120V

4 Color
DB = Dark Bronze

Options
L = Lamp (included)

Dimensions

| | A | B | C | Wt./Lbs. |
|-----|---------|----|-------|----------|
| NRG | 10.625" | 5" | 5.25" | 2.2 |

